



## 3:1 Air Operated Pump

<b>Shaft length</b>	270 MM OR 740 MM
<b>Pressure ratio</b>	3:1 Ratio
<b>Max flow rate</b>	12 L/M
<b>Air inlet size</b>	1/4" QR
<b>Outlet size</b>	1/2" BSP
<b>Max pressure</b>	5 - 8 BAR

- Air operated pump for oil transfer & dispensing
- Differential air motor ensures smooth pumping
- Suitable for engine, transmission, synthetic & hydraulic oil
- 1/2" Male BSP oil outlet port
- Supplied with adjustable 2" bung adapter
- Barrel or wall mounted option available
- High flow version up to 28 l/min

3:1 RATIO PUMPS							
Item No.	Fluid	Max Inlet Pressure	Suction Tube Material	Length	Fluid Outlet	Pressure Ratio	Max Flow Rate
AP31B	Oil	5 - 8 Bar	Carbon Steel	730mm	1/2"BSP	3:1	12L/M
AP31W	Oil	5 - 8 Bar	Carbon Steel	270mm	1/2"BSP	3:1	12L/M
AP31BH	Oil	5 - 8 Bar	Carbon Steel	730mm	1/2"BSP	3:1	28L/M

## 15 Metre Open Reel



<b>Reel Options</b>	1/2" or 3/8"
<b>Reel Type</b>	Spring Retractable
<b>Reel Length</b>	15 Metre (50ft)
<b>Inlet Type</b>	BSP Male Swivel
<b>Outlet Type</b>	BSP Male
<b>Max pressure</b>	138 Bar

- Spring retractable reel
- 15 Metre hydraulic hose
- Male BSP swivel inlet
- Male BSP hose end
- Wall mounting plate
- Corrosion resistant powder coated steel finish
- Latching of hose at any length

- 1/2" Reel suitable for use with oil, water or air
- 3/8" High pressure reel suitable for use with air, water & pressure washers

15 Metre Open Lubeworks Reels					
Item No.	Hose Length	Reel Finish	Inlet Size	Max Pressure	Compatibility
R/15H4	15 Metre	Powder Coated Steel	1/2" BSP	138 Bar	Oil, Air & Water
R/15H3	15 Metre	Powder Coated Steel	3/8" BSP	276 Bar	Air & Water